



Taski Tapi Defoam C1g

Revision: 2018-01-25

Version: 04.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Taski Tapi Defoam C1g

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses:

For professional and industrial use only.

AISE-P410 - Carpet cleaner. Semi-automatic process

Using a diluted professional cleaning solution in semi-closed cleaning equipment (AISE_CSP06)

Uses advised against: Uses other than those identified are not recommended

1.3 Details of the supplier of the safety data sheet

Diversey Europe Operations BV, Maarssebroeksedijk 2, 3542DN Utrecht, The Netherlands

Contact details

Diversey Ltd

Weston Favell Centre, Northampton NN3 8PD, United Kingdom

Tel: 01604 405311, Fax: 01604 406809

Regulatory Email: customerservice.uk@diversey.com

1.4 Emergency telephone number

For medical or environmental emergency only:

call 0800 052 0185

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flam. Liq. 2 (H225)

STOT SE 3 (H336)

Eye Irrit. 2 (H319)

2.2 Label elements



Signal word: Danger.

Contains propan-2-ol (Isopropyl Alcohol).

Hazard statements:

H225 - Highly flammable liquid and vapour.

H336 - May cause drowsiness or dizziness.

H319 - Causes serious eye irritation.

Precautionary statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P403 + P235 - Store in a well-ventilated place. Keep cool.

2.3 Other hazards

No other hazards known

The product does not meet the criteria for PBT or vPvB in accordance with Regulation (EC) No 1907/2006, Annex XIII

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Ingredient(s)	EC number	CAS number	REACH number	Classification	Notes	Weight
---------------	-----------	------------	--------------	----------------	-------	--------

Taski Tapi Defoam C1g

					percent
propan-2-ol	200-661-7	67-63-0	01-2119457558-25	Flam. Liq. 2 (H225) STOT SE 3 (H336) Eye Irrit. 2 (H319)	>= 75

* Polymer.

Workplace exposure limit(s), if available, are listed in subsection 8.1.

[1] Exempted: ionic mixture. See Regulation (EC) No 1907/2006, Annex V, paragraph 3 and 4. This salt is potentially present, based on calculation, and included for classification and labelling purposes only. Each starting material of the ionic mixture is registered, as required.

[2] Exempted: included in Annex IV of Regulation (EC) No 1907/2006.

[3] Exempted: Annex V of Regulation (EC) No 1907/2006.

[4] Exempted: polymer. See Article 2(9) of Regulation (EC) No 1907/2006.

For the full text of the H and EUH phrases mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Inhalation:

Call a POISON CENTRE, doctor or physician if you feel unwell.

Skin contact:

Wash skin with plenty of lukewarm, gently flowing water. Take off immediately all contaminated clothing and wash it before re-use. If skin irritation occurs: Get medical advice or attention.

Eye contact:

Hold eyelids apart and flush eyes with plenty of lukewarm water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs and persists, get medical attention.

Ingestion:

Rinse mouth. Immediately drink 1 glass of water. Never give anything by mouth to an unconscious person. Get medical attention or advice if you feel unwell.

Self-protection of first aider:

Consider personal protective equipment as indicated in subsection 8.2.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation:

May cause drowsiness or dizziness.

Skin contact:

No known effects or symptoms in normal use.

Eye contact:

Causes severe irritation.

Ingestion:

No known effects or symptoms in normal use.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Carbon dioxide. Dry powder. Water spray jet. Fight larger fires with water spray jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

No special hazards known.

5.3 Advice for firefighters

As in any fire, wear self contained breathing apparatus and suitable protective clothing including gloves and eye/face protection.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Turn off all sources of ignition. Ventilate the area.

6.2 Environmental precautions

Do not allow to enter drainage system, surface or ground water. Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, universal binders, sawdust).

6.4 Reference to other sections

For personal protective equipment see subsection 8.2. For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Measures to prevent fire and explosions:

Keep away from flames and hot surfaces. No smoking. Keep away from heat. Take precautionary measures against static discharges.

Measures required to protect the environment:

For environmental exposure controls see subsection 8.2.

Advices on general occupational hygiene:

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not mix with other products unless advised by Diversey. Wash hands before breaks and at the end of workday. Wash face, hands and any exposed skin

Taski Tapi Defoam C1g

thoroughly after handling. Take off immediately all contaminated clothing. Store used personal protective equipment separately. Use personal protective equipment as required. Use only with adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local and national regulations. Keep only in original container. Store in a closed container. Store in a well-ventilated place. Keep cool.

For conditions to avoid see subsection 10.4. For incompatible materials see subsection 10.5.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Workplace exposure limits**

Air limit values, if available:

Ingredient(s)	UK - Long term value(s)	UK - Short term value(s)
propan-2-ol	400 ppm 999 mg/m ³	500 ppm 1250 mg/m ³

Biological limit values, if available:

Recommended monitoring procedures, if available:

Additional exposure limits under the conditions of use, if available:

DNEL/DMEL and PNEC values**Human exposure**

DNEL oral exposure - Consumer (mg/kg bw)

Ingredient(s)	Short term - Local effects	Short term - Systemic effects	Long term - Local effects	Long term - Systemic effects
propan-2-ol	-	-	-	26

DNEL dermal exposure - Worker

Ingredient(s)	Short term - Local effects	Short term - Systemic effects (mg/kg bw)	Long term - Local effects	Long term - Systemic effects (mg/kg bw)
propan-2-ol	No data available	-	No data available	888

DNEL dermal exposure - Consumer

Ingredient(s)	Short term - Local effects	Short term - Systemic effects (mg/kg bw)	Long term - Local effects	Long term - Systemic effects (mg/kg bw)
propan-2-ol	No data available	-	-	319

DNEL inhalatory exposure - Worker (mg/m³)

Ingredient(s)	Short term - Local effects	Short term - Systemic effects	Long term - Local effects	Long term - Systemic effects
propan-2-ol	-	-	-	500

DNEL inhalatory exposure - Consumer (mg/m³)

Ingredient(s)	Short term - Local effects	Short term - Systemic effects	Long term - Local effects	Long term - Systemic effects
propan-2-ol	-	-	-	89

Environmental exposure

Environmental exposure - PNEC

Ingredient(s)	Surface water, fresh (mg/l)	Surface water, marine (mg/l)	Intermittent (mg/l)	Sewage treatment plant (mg/l)
propan-2-ol	140.9	140.9	140.9	2251

Environmental exposure - PNEC, continued

Ingredient(s)	Sediment, freshwater (mg/kg)	Sediment, marine (mg/kg)	Soil (mg/kg)	Air (mg/m ³)
propan-2-ol	552	552	28	-

8.2 Exposure controls

The following information applies for the uses indicated in subsection 1.2 of the Safety Data Sheet. If available, please refer to the product information sheet for application and handling instructions. Normal use conditions are assumed for this section.

Recommended safety measures for handling the undiluted product:

Appropriate engineering controls: The product is intended to be used in closed systems.

Taski Tapi Defoam C1g

Appropriate organisational controls: Avoid direct contact and/or splashes where possible. Train personnel.

Personal protective equipment

Eye / face protection: Safety glasses are not normally required. However, their use is recommended in those cases where splashes may occur when handling the product (EN 166).

Hand protection: No special requirements under normal use conditions.

Body protection: No special requirements under normal use conditions.

Respiratory protection: No special requirements under normal use conditions.

Environmental exposure controls: Should not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Information in this section refers to the product, unless it is specifically stated that substance data is listed

Physical State: Liquid

Colour: Clear, Colourless

Odour: Product specific

Odour threshold: Not applicable

pH:

Melting point/freezing point (°C): Not determined

Initial boiling point and boiling range (°C): Not determined

Method / remark

Not relevant to classification of this product

Substance data, boiling point

Ingredient(s)	Value (°C)	Method	Atmospheric pressure (hPa)
propan-2-ol	82	Method not given	1013

Method / remark

closed cup

Flash point (°C): ≈ 15

Sustained combustion: Not applicable.

(UN Manual of Tests and Criteria, section 32, L.2)

Evaporation rate: Not determined

Flammability (solid, gas): Not determined

Upper/lower flammability limit (%): Not determined

Substance data, flammability or explosive limits, if available:

Ingredient(s)	Lower limit (% vol)	Upper limit (% vol)
propan-2-ol	2	13

Method / remark

Vapour pressure: Not determined

Substance data, vapour pressure

Ingredient(s)	Value (Pa)	Method	Temperature (°C)
propan-2-ol	4200	Method not given	20

Method / remark

Vapour density: Not determined

Relative density: ≈ 0.80 (20 °C)

Solubility in / Miscibility with Water: Fully miscible

Substance data, solubility in water

Ingredient(s)	Value (g/l)	Method	Temperature (°C)
propan-2-ol	Soluble	Method not given	

Substance data, partition coefficient n-octanol/water (log Kow): see subsection 12.3

Method / remark

Autoignition temperature: Not determined

Decomposition temperature: Not applicable.

Viscosity: Not determined

Explosive properties: Not explosive. Vapours may form explosive mixtures with air.

Oxidising properties: Not oxidising.

9.2 Other information

Surface tension (N/m): Not determined

Corrosion to metals: Not corrosive

Not relevant to classification of this product

Substance data, dissociation constant, if available:

Taski Tapi Defoam C1g

SECTION 10: Stability and reactivity**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal storage and use conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known under normal storage and use conditions.

10.4 Conditions to avoid

None known under normal storage and use conditions.

10.5 Incompatible materials

None known under normal use conditions.

10.6 Hazardous decomposition products

None known under normal storage and use conditions.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Mixture data:

Relevant calculated ATE(s):

ATE - Oral (mg/kg): 3900

Substance data, where relevant and available, are listed below:

Acute toxicity

Acute oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)
propan-2-ol	LD ₅₀	3570	Rat	Method not given	

Acute dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)
propan-2-ol	LD ₅₀	> 2000	Rabbit	Method not given	

Acute inhalative toxicity

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
propan-2-ol	LC ₅₀	> 25 (vapour)	Rat	OECD 403 (EU B.2)	6

Irritation and corrosivity

Skin irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
propan-2-ol	Not irritant	Rabbit	OECD 404 (EU B.4)	

Eye irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
propan-2-ol	Irritant	Rabbit	OECD 405 (EU B.5)	

Respiratory tract irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
propan-2-ol	No data available			

Sensitisation

Sensitisation by skin contact

Ingredient(s)	Result	Species	Method	Exposure time (h)
propan-2-ol	Not sensitising	Guinea pig	OECD 406 (EU B.6) / Buehler test	

Sensitisation by inhalation

Ingredient(s)	Result	Species	Method	Exposure time
propan-2-ol	No data available			

Taski Tapi Defoam C1g

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Mutagenicity

Ingredient(s)	Result (in-vitro)	Method (in-vitro)	Result (in-vivo)	Method (in-vivo)
propan-2-ol	No evidence for mutagenicity, negative test results No evidence of genotoxicity, negative test results	OECD 471 (EU B.12/13)	No evidence of genotoxicity, negative test results	OECD 474 (EU B.12)

Carcinogenicity

Ingredient(s)	Effect
propan-2-ol	No data available

Toxicity for reproduction

Ingredient(s)	Endpoint	Specific effect	Value (mg/kg bw/d)	Species	Method	Exposure time	Remarks and other effects reported
propan-2-ol			No data available				

Repeated dose toxicity

Sub-acute or sub-chronic oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
propan-2-ol		No data available				

Sub-chronic dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
propan-2-ol		No data available				

Sub-chronic inhalation toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
propan-2-ol		No data available				

Chronic toxicity

Ingredient(s)	Exposure route	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time	Specific effects and organs affected	Remark
propan-2-ol			No data available					

STOT-single exposure

Ingredient(s)	Affected organ(s)
propan-2-ol	No data available

STOT-repeated exposure

Ingredient(s)	Affected organ(s)
propan-2-ol	No data available

Aspiration hazard

Substances with an aspiration hazard (H304), if any, are listed in section 3. If relevant, see section 9 for dynamic viscosity and relative density of the product.

Potential adverse health effects and symptoms

Effects and symptoms related to the product, if any, are listed in subsection 4.2.

SECTION 12: Ecological information**12.1 Toxicity**

No data is available on the mixture.

Substance data, where relevant and available, are listed below:

Aquatic short-term toxicity

Aquatic short-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
propan-2-ol	LC ₅₀	> 100	<i>Pimephales promelas</i>	Method not given	48

Aquatic short-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
---------------	----------	--------------	---------	--------	-------------------

Taski Tapi Defoam C1g

propan-2-ol	EC ₅₀	> 100	<i>Daphnia magna Straus</i>	Method not given	48
-------------	------------------	-------	-----------------------------	------------------	----

Aquatic short-term toxicity - algae

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
propan-2-ol	EC ₅₀	> 100	<i>Scenedesmus quadricauda</i>	Method not given	72

Aquatic short-term toxicity - marine species

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (days)
propan-2-ol		No data available			-

Impact on sewage plants - toxicity to bacteria

Ingredient(s)	Endpoint	Value (mg/l)	Inoculum	Method	Exposure time
propan-2-ol	EC ₅₀	> 1000	<i>Activated sludge</i>	Method not given	

Aquatic long-term toxicity

Aquatic long-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
propan-2-ol		No data available				

Aquatic long-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
propan-2-ol		No data available				

Aquatic toxicity to other aquatic benthic organisms, including sediment-dwelling organisms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw sediment)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity

Terrestrial toxicity - soil invertebrates, including earthworms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity - plants, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity - birds, if available:

Ingredient(s)	Endpoint	Value	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity - beneficial insects, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity - soil bacteria, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

12.2 Persistence and degradability

Abiotic degradation

Abiotic degradation - photodegradation in air, if available:

Taski Tapi Defoam C1g

Abiotic degradation - hydrolysis, if available:

Abiotic degradation - other processes, if available:

Biodegradation

Ready biodegradability - aerobic conditions

Ingredient(s)	Inoculum	Analytical method	DT ₅₀	Method	Evaluation
propan-2-ol			95 % in 21 day(s)	OECD 301E	Readily biodegradable

Ready biodegradability - anaerobic and marine conditions, if available:

Degradation in relevant environmental compartments, if available:

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log K_{ow})

Ingredient(s)	Value	Method	Evaluation	Remark
propan-2-ol	0.05	OECD 107	No bioaccumulation expected	

Bioconcentration factor (BCF)

Ingredient(s)	Value	Species	Method	Evaluation	Remark
propan-2-ol	No data available				

12.4 Mobility in soil

Adsorption/Desorption to soil or sediment

Ingredient(s)	Adsorption coefficient Log K _{oc}	Desorption coefficient Log K _{oc} (des)	Method	Soil/sediment type	Evaluation
propan-2-ol	No data available				Potential for mobility in soil, soluble in water

12.5 Results of PBT and vPvB assessment

Substances that fulfill the criteria for PBT/vPvB, if any, are listed in section 3.

12.6 Other adverse effects

No other adverse effects known.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste from residues / unused products:

The concentrated contents or contaminated packaging should be disposed of by a certified handler or according to the site permit. Release of waste to sewers is discouraged. The cleaned packaging material is suitable for energy recovery or recycling in line with local legislation.

European Waste Catalogue:

16 03 05* - organic wastes containing dangerous substances.

Empty packaging

Recommendation:

Dispose of observing national or local regulations.

Suitable cleaning agents:

Water, if necessary with cleaning agent.

SECTION 14: Transport information

Land transport (ADR/RID), Sea transport (IMDG), Air transport (ICAO-TI / IATA-DGR)

14.1 UN number: 1219

14.2 UN proper shipping name:

Isopropanol (isopropyl alcohol) , solution

14.3 Transport hazard class(es):

Class: 3

Label(s): 3

14.4 Packing group: II

14.5 Environmental hazards:

Environmentally hazardous: No

Marine pollutant: No

14.6 Special precautions for user: None known.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: The product is not transported in bulk tankers.

Other relevant information:

ADR

Taski Tapi Defoam C1g

Classification code: F1

Tunnel restriction code: D/E

Hazard identification number: 33

IMO/IMDG

EmS: F-E, S-D

The product has been classified, labelled and packaged in accordance with the requirements of ADR and the provisions of the IMDG Code. Transport regulations include special provisions for certain classes of dangerous goods packed in limited quantities.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations:**

- Regulation (EC) No 1272/2008 - CLP
- Regulation (EC) No. 1907/2006 - REACH

Authorisations or restrictions (Regulation (EC) No 1907/2006, Title VII respectively Title VIII): Not applicable.

Ingredients according to EC Detergents Regulation 648/2004**15.2 Chemical safety assessment**

A chemical safety assessment has not been carried out on the mixture

SECTION 16: Other information

The information in this document is based on our best present knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally binding contract

SDS code: MSDS4746

Version: 04.1

Revision: 2018-01-25

Reason for revision:

This data sheet contains changes from the previous version in section(s):, 2, 3, 16

Classification procedure

The classification of the mixture is in general based on calculation methods using substance data, as required by Regulation (EC) No 1272/2008. If for certain classifications data on the mixture is available or for example bridging principles or weight of evidence can be used for classification, this will be indicated in the relevant sections of the Safety Data Sheet. See section 9 for physical chemical properties, section 11 for toxicological information and section 12 for ecological information.

Full text of the H and EUH phrases mentioned in section 3:

- H225 - Highly flammable liquid and vapour.
- H319 - Causes serious eye irritation.
- H336 - May cause drowsiness or dizziness.

Abbreviations and acronyms:

- AISE - The international Association for Soaps, Detergents and Maintenance Products
- DNEL - Derived No Effect Limit
- EUH - CLP Specific hazard statement
- PBT - Persistent, Bioaccumulative and Toxic
- PNEC - Predicted No Effect Concentration
- REACH number - REACH registration number, without supplier specific part
- vPvB - very Persistent and very Bioaccumulative
- ATE - Acute Toxicity Estimate

End of Safety Data Sheet