



## PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47570-00005	Date of first issue: 13.01.2015

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : PURELL® Hand sanitising gel VF481™

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Hand Sanitizer

#### 1.3 Details of the supplier of the safety data sheet

Company : GOJO Industries-Europe Ltd.  
Units 5 & 6, Stratus Park  
MK10 0DE Brinklow, Milton Keynes

Telephone : +44(0) 1908588444

Telefax : +44(0) 1908588445

E-mail address of person responsible for the SDS : infoUK@gojo.com

#### 1.4 Emergency telephone number

+44(0) 8445605135

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting effects.

##### Classification (67/548/EEC, 1999/45/EC)

Flammable R10: Flammable.

Irritant R36: Irritating to eyes.



Dangerous for the environment R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## PURELL® Hand sanitising gel VF481™

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	 
Signal word	:	Warning
Hazard statements	:	H226      Flammable liquid and vapour. H319      Causes serious eye irritation. H412      Harmful to aquatic life with long lasting effects.
Precautionary statements	:	<b>Prevention:</b> P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233      Keep container tightly closed. P273      Avoid release to the environment. P280      Wear protective gloves/ protective clothing/ eye protection/ face protection.  <b>Response:</b> P303 + P361 + P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P337 + P313      If eye irritation persists: Get medical advice/ attention.

### 2.3 Other hazards

Vapours may form explosive mixture with air.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical Name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Ethanol	64-17-5 200-578-6	F; R11 Xi; R36	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 50 - < 70
Propan-2-ol	67-63-0 200-661-7	F; R11 Xi; R36 R67	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 3 - < 10
Copper Gluconate	527-09-3 208-408-2	Xn; R22 N; R50/53	Acute Tox. 4; H302 Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0.025 - < 0.1



## PURELL® Hand sanitising gel VF481™

Version 2.0	Revision Date: 03.06.2015	MSDS Number: 47570-00005	Date of last issue: 10.03.2015 Date of first issue: 13.01.2015
----------------	------------------------------	-----------------------------	---

			H410	
--	--	--	------	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet



## PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47570-00005	Date of first issue: 13.01.2015

---

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and dis-



## PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47570-00005	Date of first issue: 13.01.2015

---

posal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |  |
|-------------------------|--|
| Technical measures      | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.  |
| Local/Total ventilation | : Use with local exhaust ventilation.<br>Use only in an area equipped with explosion proof exhaust ventilation.  |
| Advice on safe handling | : Avoid inhalation of vapour or mist.<br>Do not swallow.<br>Do not get in eyes.<br>Avoid prolonged or repeated contact with skin.<br>Handle in accordance with good industrial hygiene and safety practice.<br>Non-sparking tools should be used.<br>Keep container tightly closed.<br>Keep away from heat and sources of ignition.<br>Take precautionary measures against static discharges.<br>Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures        | : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.   |

### 7.2 Conditions for safe storage, including any incompatibilities

- |   |   |
|---|---|
| Requirements for storage areas and containers | : Keep in properly labelled containers. Keep tightly closed.<br>Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.   |
| Advice on common storage                      | : Do not store with the following product types:<br>Strong oxidizing agents<br>Organic peroxides<br>Flammable solids<br>Pyrophoric liquids<br>Pyrophoric solids<br>Self-heating substances and mixtures<br>Substances and mixtures, which in contact with water, emit flammable gases |



**PURELL® Hand sanitising gel VF481™**

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

Explosives  
Gases

**7.3 Specific end use(s)**

Specific use(s) : No data available

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m <sup>3</sup>	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			
Propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m <sup>3</sup>	GB EH40
		STEL	500 ppm 1,250 mg/m <sup>3</sup>	GB EH40

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**

Ethanol	: End Use: Workers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 1900 mg/m <sup>3</sup> End Use: Workers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 343 mg/kg bw/day End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 950 mg/m <sup>3</sup> End Use: Consumers Exposure routes: Inhalation Potential health effects: Acute local effects Value: 950 mg/m <sup>3</sup> End Use: Consumers Exposure routes: Skin contact Potential health effects: Long-term systemic effects Value: 206 mg/kg bw/day End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 114 mg/m <sup>3</sup> End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 87 mg/kg bw/day
---------	---



**PURELL® Hand sanitising gel VF481™**

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

Propan-2-ol : End Use: Workers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 500 mg/m<sup>3</sup>  
End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 888 mg/kg bw/day  
End Use: Consumers  
Exposure routes: Inhalation  
Potential health effects: Long-term systemic effects  
Value: 89 mg/m<sup>3</sup>  
End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 319 mg/kg bw/day  
End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: Long-term systemic effects  
Value: 26 mg/kg bw/day

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:**

Ethanol : Fresh water  
Value: 0.96 mg/l  
Marine water  
Value: 0.79 mg/l  
Intermittent use/release  
Value: 2.75 mg/l  
Sewage treatment plant  
Value: 580 mg/l  
Fresh water sediment  
Value: 3.6 mg/kg  
Marine sediment  
Value: 2.9 mg/kg  
Soil  
Value: 0.63 mg/kg  
Oral  
Value: 720 mg/kg  
Propan-2-ol : Fresh water  
Value: 140.9 mg/l  
Marine water  
Value: 140.9 mg/l  
Intermittent use/release  
Value: 140.9 mg/l  
Sewage treatment plant  
Value: 2251 mg/l  
Fresh water sediment  
Value: 552 mg/kg  
Marine sediment  
Value: 552 mg/kg  
Soil  
Value: 28 mg/kg  
Oral  
Value: 160 mg/kg



## PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47570-00005	Date of first issue: 13.01.2015

---

### 8.2 Exposure controls

#### Engineering measures

Minimize workplace exposure concentrations.  
Use only in an area equipped with explosion proof exhaust ventilation.  
Use with local exhaust ventilation.

#### Personal protective equipment

- |                          |   |
|--------------------------|---|
| Eye protection           | : Wear the following personal protective equipment:<br>Safety goggles   |
| Hand protection          |   |
| Material                 | : Impervious gloves<br>Flame retardant gloves   |
| Remarks                  | : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. |
| Skin and body protection | : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.<br>Wear the following personal protective equipment:<br>Flame retardant antistatic protective clothing.<br>Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).   |
| Respiratory protection   | : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.   |
| Filter type              | : Organic vapour type (A)   |
- 

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- |                              |                           |
|------------------------------|---------------------------|
| Appearance                   | : liquid                  |
| Colour                       | : clear, Hazy, blue green |
| Odour                        | : alcohol-like            |
| Odour Threshold              | : No data available       |
| pH                           | : 3.5 - 5.2               |
| Melting point/freezing point | : No data available       |
-





## PURELL® Hand sanitising gel VF481™

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

---

Initial boiling point and boiling range	: 75.00 °C
Flash point	: 26.5 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.8850 g/cm <sup>3</sup>
Solubility(ies) Water solubility	: soluble
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: The substance or mixture is not classified self-reactive.
Viscosity Viscosity, kinematic	: 80 - 600 mm <sup>2</sup> /s (20 °C)
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

### 9.2 Other information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Flammable liquid and vapour.



## PURELL® Hand sanitising gel VF481™

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

---

Vapours may form explosive mixture with air.  
Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Ethanol:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

##### **Propan-2-ol:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 72.6 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

##### **Copper Gluconate:**

Acute oral toxicity : LD50 (Rat): 1,710 mg/kg

#### **Skin corrosion/irritation**

Not classified based on available information.

#### Product:

Result: No skin irritation



## PURELL® Hand sanitising gel VF481™

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

---

### Components:

#### **Ethanol:**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

#### **Propan-2-ol:**

Species: Rabbit  
Result: No skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### Components:

#### **Ethanol:**

Species: Rabbit  
Method: OECD Test Guideline 405  
Result: Irritation to eyes, reversing within 21 days

#### **Propan-2-ol:**

Species: Rabbit  
Result: Irritation to eyes, reversing within 21 days

### **Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
Respiratory sensitisation: Not classified based on available information.

### Product:

Assessment: Does not cause skin sensitisation.

### Components:

#### **Ethanol:**

Test Type: Local lymph node assay (LLNA)  
Exposure routes: Skin contact  
Species: Mouse  
Result: negative

#### **Propan-2-ol:**

Test Type: Buehler Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: negative

### **Germ cell mutagenicity**

Not classified based on available information.

### Components:

#### **Ethanol:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative



## PURELL® Hand sanitising gel VF481™

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

---

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

**Propan-2-ol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

**Copper Gluconate:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

**Carcinogenicity**

Not classified based on available information.

**Components:**

**Propan-2-ol:**

Species: Rat  
Application Route: inhalation (vapour)  
Exposure time: 104 weeks  
Method: OECD Test Guideline 451  
Result: negative

**Reproductive toxicity**

Not classified based on available information.

**Components:**

**Ethanol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 416  
Result: negative

**Propan-2-ol:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on foetal develop-  
ment : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative



## PURELL® Hand sanitising gel VF481™

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

---

### **Copper Gluconate:**

Effects on fertility : Species: Rat  
Application Route: Ingestion  
Result: negative

### **STOT - single exposure**

Not classified based on available information.

### **Components:**

#### **Propan-2-ol:**

Assessment: May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Repeated dose toxicity**

### **Components:**

#### **Ethanol:**

Species: Rat  
NOAEL: 2,400 mg/kg  
Application Route: Ingestion  
Exposure time: 2 y

#### **Propan-2-ol:**

Species: Rat  
NOAEL: 5000 ppm  
Application Route: inhalation (vapour)  
Exposure time: 104 w  
Method: OECD Test Guideline 413

### **Aspiration toxicity**

Not classified based on available information.

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

### **Components:**

#### **Ethanol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to bacteria : EC50 (Photobacterium phosphoreum): 32.1 mg/l

---

## PURELL® Hand sanitising gel VF481™

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

Exposure time: 0.25 h  
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 9.6 mg/l  
Exposure time: 9 d  
Species: Daphnia magna (Water flea)

### Propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 10,000 mg/l  
Exposure time: 96 h  
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 24 h  
Toxicity to bacteria : EC50 (Pseudomonas putida): > 1,050 mg/l  
Exposure time: 16 h

### Copper Gluconate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.07 - 0.7 mg/l  
Exposure time: 96 h  
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 0.7 - 2.1 mg/l  
Exposure time: 48 h  
Toxicity to algae : ErC50 (Scenedesmus capricornutum (fresh water algae)): 0.1 - 1 mg/l  
Exposure time: 72 h  
NOEC (Pseudokirchneriella subcapitata (green algae)): 0.1 - 1 mg/l  
Exposure time: 72 h  
M-Factor (Acute aquatic toxicity) : 10  
Toxicity to fish (Chronic toxicity) : NOEC: > 1 - 10 µg/l  
Remarks: Based on data from similar materials  
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: > 1 - 10 µg/l  
Remarks: Based on data from similar materials  
M-Factor (Chronic aquatic toxicity) : 10

## 12.2 Persistence and degradability

### Components:

#### Ethanol:

Biodegradability : Result: Readily biodegradable  
Biodegradation: 84 %  
Exposure time: 20 d

#### Propan-2-ol:



## PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47570-00005	Date of first issue: 13.01.2015

---

Biodegradability : Result: rapidly degradable

### 12.3 Bioaccumulative potential

#### Components:

##### **Ethanol:**

Partition coefficient: n-octanol/water : log Pow: -0.35

##### **Propan-2-ol:**

Partition coefficient: n-octanol/water : log Pow: 0.05

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14: Transport information

### 14.1 UN number

ADN : UN 1987

ADR : UN 1987

RID : UN 1987

IMDG : UN 1987

IATA : UN 1987

### 14.2 UN proper shipping name

ADN : ALCOHOLS, N.O.S.

---



## PURELL® Hand sanitising gel VF481™

Version 2.0      Revision Date: 03.06.2015      MSDS Number: 47570-00005      Date of last issue: 10.03.2015  
Date of first issue: 13.01.2015

---

(Ethanol, Propan-2-ol)  
**ADR** : ALCOHOLS, N.O.S.  
(Ethanol, Propan-2-ol)  
**RID** : ALCOHOLS, N.O.S.  
(Ethanol, Propan-2-ol)  
**IMDG** : ALCOHOLS, N.O.S.  
**II** (Ethanol, Propan-2-ol)  
**IATA** : Alcohols, n.o.s.  
(Ethanol, Propan-2-ol)

### 14.3 Transport hazard class(es)

**ADN** : 3  
**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-D

**IATA**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids





**PURELL® Hand sanitising gel VF481™**

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47570-00005	Date of first issue: 13.01.2015

**14.5 Environmental hazards**

**ADN**

Environmentally hazardous : no

**ADR**

Environmentally hazardous : no

**RID**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

Not applicable

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Remarks : Not applicable for product as supplied.

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

		Quantity 1	Quantity 2
6	Flammable.	5,000 t	50,000 t

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c	FLAMMABLE LIQUIDS	5,000 t	50,000 t
-----	-------------------	---------	----------

34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alterna-	2,500 t	25,000 t
----	---	---------	----------



## PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47570-00005	Date of first issue: 13.01.2015

---

tive fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: < 75 %

### The components of this product are reported in the following inventories:

AICS : All ingredients listed or exempt.

### Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

### 15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

---

## SECTION 16: Other information

### Full text of R-Phrases

R11 : Highly flammable.  
R22 : Harmful if swallowed.  
R36 : Irritating to eyes.  
R50/53 : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R67 : Vapours may cause drowsiness and dizziness.

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H302 : Harmful if swallowed.  
H319 : Causes serious eye irritation.  
H336 : May cause drowsiness or dizziness.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Acute aquatic toxicity  
Aquatic Chronic : Chronic aquatic toxicity  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
STOT SE : Specific target organ toxicity - single exposure  
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits  
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)



## PURELL® Hand sanitising gel VF481™

Version	Revision Date:	MSDS Number:	Date of last issue: 10.03.2015
2.0	03.06.2015	47570-00005	Date of first issue: 13.01.2015

---

GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN